

LOC I-MCN

109.5

APP CRS

054°

Rwy Ldg

6221

TDZE

344

Apt Elev

354

ILS or LOC RWY 5

MIDDLE GEORGIA RGNL (MCN)

DME and RADAR required.

⚠

DME from MCN VORTAC. Simultaneous reception of I-MCN and MCN DME required. For inop ALS, increase S-ILS 5 Cat E visibility to RVR 4000 and S-LOC 5 Cats C, D, and E visibilities to 1 3⁄8 SM.
* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH: Climb to 800 then climbing right turn to 3000 on heading 090° and DBN VORTAC R-314 to TRUKR/DBN VORTAC 15 DME/RADAR and hold.

ATIS	ATLANTA APP CON ★	MACON TOWER ★	GND CON	UNICOM
120.775	124.2 279.6	128.2 (CTAF) 0 257.8	121.65	122.95

MSA MCN 25 NM

LOCALIZER 109.5

I-MCN

MACON Chan 89 MCN (114.2)

BRROS MCN 2.9 576±

ALLMN MCN 5.8 RADAR

(IF/IAF) BLSKY MCN 11.7 RADAR

HOLD 4800 2100

2100 NoPT 054° (10.2)

234°

2000 054° (5.9)

1 min

R-321

2100 NoPT 321° (26.6)

Procedure NA for arrivals at VNA VORTAC on V243 northwest bound.

(IAF) VIENNA 116.5 VNA Chan 112

MISSED APCH FIX

TRUKR DBN 15 RADAR

113.1 DBN Chan 78

R-314

ELEV 354

TDZE 344

One Minute Holding Pattern

BLSKY MCN 11.7 RADAR

4800 2100

234°

054°

GS 3.00° TCH 56

800

3000

DBN R-314

TRUKR DBN 15

ALLMN MCN 5.8 RADAR

BRROS MCN 2.9

MCN 2.1

MCN 0.8

2000

1080

5.9 NM

2.9 NM

0.8 NM

1.4 NM

CATEGORY	A	B	C	D	E
S-ILS 5*	544/24 200 (200-1⁄2)				
S-LOC 5	840/24	496 (500-1⁄2)	840/50 496 (500-1)		
CIRCLING	900-1	546 (600-1)	920-1 1⁄2 566 (600-1 1⁄2)	1120-2 1⁄2 766 (800-2 1⁄2)	1180-3 826 (900-3)

HIRL Rwy 5-23

MIRL Rwy 14-32

REIL Rwy 23 and 32

MACON, GEORGIA

Amtd 4 08SEP22

32°42'N-83°39'W

MIDDLE GEORGIA RGNL (MCN)

ILS or LOC RWY 5