

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>42522</b><br><b>W18A</b> | APP CRS<br><b>185°</b> | Rwy Ldg <b>8606</b><br>TDZE <b>864</b><br>Apt Elev <b>887</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

RNAV (GPS) RWY 18

DANE COUNTY RGNL/TRUAX FLD (MSN)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1½ mile and LNAV Cat C/D visibility to 1½ miles.  
\*\* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:  
Climb to 3000 direct  
DEKEY and hold.

|                             |                                         |                                               |                               |                         |
|-----------------------------|-----------------------------------------|-----------------------------------------------|-------------------------------|-------------------------|
| ATIS<br><b>124.65 278.3</b> | MADISON APP CON★<br><b>135.45 343.7</b> | MADISON TOWER★<br><b>119.3 (CTAF) 0 257.8</b> | GND CON<br><b>121.9 348.6</b> | UNICOM<br><b>122.95</b> |
|-----------------------------|-----------------------------------------|-----------------------------------------------|-------------------------------|-------------------------|

|                 |          |                 |
|-----------------|----------|-----------------|
| ELEV <b>887</b> | <b>D</b> | TDZE <b>864</b> |
|-----------------|----------|-----------------|

|              |                      |                    |                      |                      |
|--------------|----------------------|--------------------|----------------------|----------------------|
| 3000         | DEKEY                | AYECO              | 4 NM Holding Pattern |                      |
| *LNAV only   | *1.4 NM to RW18      | RUKIY 2500         | GATNE 2700           |                      |
| 1.4          | 3.6 NM               | 3.2 NM             | 3.7 NM               |                      |
| CATEGORY     | A                    | B                  | C                    | D                    |
| LPV DA **    | 1064/24 200 (200-½)  |                    |                      |                      |
| LNAV/VNAV DA | 1360-1¼ 496 (500-1¼) |                    |                      |                      |
| LNAV MDA     | 1360/24              | 496 (500-½)        | 1360/55              | 496 (500-1)          |
| CIRCLING     | 1420-1 533 (600-1)   | 1460-1 573 (600-1) | 1460-1½ 573 (600-½)  | 1700-2¾ 813 (900-2¾) |

MADISON, WISCONSIN  
Amdt 2F 07DEC17

43°08'N-89°20'W

DANE COUNTY RGNL/TRUAX FLD (MSN)

RNAV (GPS) RWY 18

EC-3, 22 JAN 2026 to 19 FEB 2026

EC-3, 22 JAN 2026 to 19 FEB 2026