


LOC I-001	APP CRS	Rwy Ldg	9320
109.9	180°	TDZE	295
		Apt Elev	341

ILS or LOC RWY 18R
FREDERICK W SMITH INTL (MEM)

Radar required for procedure entry, DME or RADAR required.		MALSR	MISSED APPROACH: Climb to 900 then climbing right turn to 5000 on MEM VORTAC R-212 to JEPOB INT/UJM 20 DME and hold.
Simultaneous approach authorized. For inop ALS, increase S-ILS 18R Cat E visibility to RVR 4000, S-LOC 18R Cat E visibility to 2 SM, SAAMM fix minimums, increase S-LOC 18R Cat E visibility to 1½ SM.		AS	
MEMPHIS APP CON		MEMPHIS TOWER	
119.1 291.6 (176°-355°)		118.3 257.8 (Rwy 9-27)	
125.8 338.3 (356°-175°)		119.7 257.8 (Rwys 18C-36C, 18L-36R)	
		128.425 257.8 (Rwy 18R-36L)	
		GND CON	
		121.0 379.2 (Rwy 9-27)	
		121.9 379.2 (Rwys 18C-36C, 18L-36R)	
		121.65 379.2 (Rwy 18R-36L)	



MCVEY MEM 14.8 RADAR		BRALE MEM 10.3 RADAR	ELVIS MEM 7.2 RADAR	SAAMM MEM 3.8 RADAR	MEM 2.1	900	5000	JEPOB
4000		3000	2000	1000				
GS 3.00° TCH 52								
4.5 NM		3.1 NM	3.4 NM	1.7 NM				
CATEGORY	A	B	C	D	E			
S-ILS 18R	495/18 200 (200-½)				495/24 200 (200-½)			
S-LOC 18R	840/24	545 (500-½)	840/50 545 (500-1)	840/60 545 (500-1¼)	840-1½ 545 (500-1½)			
CIRCLING	940-1	599 (600-1)	940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)	1140-2¾ 799 (800-2¾)			
SAAMM FIX MINIMUMS (DME OR RADAR REQUIRED)								
S-LOC 18R	700/24	405 (400-½)	700/40 405 (400-¾)	700/50 405 (400-1)				
CIRCLING	940-1	599 (600-1)	940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)	1140-2¾ 799 (800-2¾)			
						ELEV 341	TDZE 295	
						FAC to MAP 5.1 NM		
						Knots	60	90
						Min:Sec	5:06	3:24
							2:33	2:02
							1:42	

SE-1, 22 JAN 2026 to 19 FEB 2026

SE-1, 22 JAN 2026 to 19 FEB 2026