

WAAS CH 93607 W27A	APP CRS 273°	Rwy Ldg TDZE Apt Elev	8946 292 341
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 27
FREDERICK W SMITH INTL (MEM)

RNP APCH - GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 54°C. For inop ALS, increase LNAV Cat C and D visibility to 1 3/8 SM.
A *RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS



MISSED APPROACH: Climb to 5000 direct AVADE and on track 279° to GOWRI and hold, continue climb-in-hold to 5000.


MEMPHIS APP CON

119.1	291.6	(176°-355°)
125.8	338.3	(356°-175°)


MEMPHIS TOWER		
(Rwy 9-27)	118.3	257.8
(Rwys 18C-36C, 18L-36R)	119.7	257.8
(Rwy 18R-36L)	128.425	257.8

	GND CON		
(Rwy 9-27)		121.0	379.2
(Rwys 18C-36C, 18L-36R)		121.9	379.2
(Rwy 18R-36L)		121.65	379.2

D-ATIS
127.75



ELEV 341	D	TDZE 292
----------	----------	----------



TDZL/RCLS Rwy 18L, 18C,
18R, 36R, 36C, and 36L
HIRL a|| Rwy

CATEGORY	A	B	C	D
LPV DA *		492/24	200 (200-½)	
LNAV/ VNAV	DA	745/50	453 (500-1)	
LNAV MDA	800/24	508 (500-½)	800/55	508 (500-1)
CIRCLING	940-1	599 (600-1)	940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)