

WAAS CH 62828 W14A	APP CRS 146°	Rwy Ldg TDZE Apt Elev 705
--	------------------------	--

RNAV (GPS) RWY 14

ST PAUL DOWNTOWN HOLMAN FLD (STP)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). Rwy 14 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV Cats C and D to 2 ½ SM.

MALSR

MISSED APPROACH: (Do not exceed 250K until WHISK) Climb to 1700 then climbing left turn to 3000 direct WHISK and hold.

ATIS 118.35	MINNEAPOLIS APP CON 121.2 335.65	ST. PAUL TOWER ★ 119.1(CTAF) 257.8	GND CON 121.675	UNICOM 122.95
-----------------------	--	--	---------------------------	-------------------------

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 50).				
TEPAW MRANN 3000 2900 143° 146° GP 3.00° TCH 42 5 NM 4.4 NM 2.4 NM RWY 14 * 2.4 NM to RWY 14 * LNAV only.				
CATEGORY	A	B	C	D
LPV DA	955/40		250 (300-¾)	
LNAV/VNAV DA	1511-2½		806 (900-2½)	
LNAV MDA	1520/40	815 (900-¾)	1520-1⅞	815 (900-1⅞)
CIRCLING	1580-1¼	875 (900-1¼)	1580-2½ 875 (900-2½)	1580-2¾ 875 (900-2¾)

ELEV 705

D

TDZE 705

MRL Rwy 9-27
REIL Rwy 31
REIL Rwy 32
HIRL Rwy 14-32 and 13-31

ST PAUL, MINNESOTA
Amdt 1B 17AUG17

ST PAUL DOWNTOWN HOLMAN FLD (STP)

44°56'N-93°04'W

RNAV (GPS) RWY 14