

|                                        |                        |                             |                                         |
|----------------------------------------|------------------------|-----------------------------|-----------------------------------------|
| WAAS<br>CH <b>42515</b><br><b>W13A</b> | APP CRS<br><b>126°</b> | Rwy Ldg<br>TDZE<br>Apt Elev | <b>7032</b><br><b>590</b><br><b>590</b> |
|----------------------------------------|------------------------|-----------------------------|-----------------------------------------|

RNAV (GPS) RWY 13

QUAD CITIES INTL (MLI)

⚠ Circling to Rwy 5 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.6°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Davenport altimeter setting and increase LPV DA to 955 feet, LNAV/VNAV DA to 1339 feet and all MDA 60 feet; increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cats C and D, and Circling Cats C and D visibility ¼ SM. Rwy 13 helicopter reduction below ¾ SM NA. VDP and Baro-VNAV NA when using Davenport altimeter setting.

MISSED APPROACH:  
Climb to 3000 direct  
ARACI and on track  
195° to MIGNE and  
on track 275° to MZV  
VOR/DME and hold.

|                      |                                            |                                                |                         |                         |
|----------------------|--------------------------------------------|------------------------------------------------|-------------------------|-------------------------|
| ATIS<br><b>121.2</b> | QUAD CITY APP CON ★<br><b>125.95 257.8</b> | QUAD CITY TOWER ★<br><b>119.4(CTAF) 269.55</b> | GND CON<br><b>121.9</b> | UNICOM<br><b>122.95</b> |
|----------------------|--------------------------------------------|------------------------------------------------|-------------------------|-------------------------|

