

LOC/DME I-EXR
110.9
Chan **46**

APP CRS
176°

Rwy Ldg
TDZE **1287**
Apt Elev **1296**

ILS or LOC RWY 17L

OKC WILL ROGERS INTL (OKC)

▼

ASR

Simultaneous approach authorized. Inop table does not apply to S-ILS 17L. For inop ALS, increase S-LOC 17L visibilities Cats A and B to RVR 5500, and Cat E to 1 3⁄8 SM. RURIQ Fix Minimums: For inop ALS, increase S-LOC 17L visibilities Cats A and B to RVR 5500, and Cats C, D, and E to RVR 6000. Autopilot coupled approach NA below 1480.

MALSR

MISSED APPROACH: Climb to 5000 on heading 180° and on IRW VORTAC R-168 to JAVXE/IRW 11.6 DME and hold, continue climb-in-hold to 5000.

D-ATIS 125.85	OKE CITY APP CON 124.6 266.8	ROGERS TOWER 119.35 269.45	GND CON 121.9 348.6
-------------------------	--	--------------------------------------	-------------------------------

One Minute Holding Pattern

Use I-EXR DME when on the localizer course.

CATEGORY	A	B	C	D	E
S-ILS 17L	1487/40 200 (200-3⁄4)				
S-LOC 17L	1740/40	453 (500-3⁄4)	1740/45	453 (500-7⁄8)	
CIRCLING	1740-1 444 (500-1)	1760-1 464 (500-1)	1960-1 3⁄4 664 (700-1 3⁄4)	2000-2 1⁄4 704 (800-2 1⁄4)	2240-3 944 (1000-3)
RURIQ FIX MINIMUMS					
S-LOC 17L	1680/40 393 (400-3⁄4)				
CIRCLING	1740-1 444 (500-1)	1760-1 464 (500-1)	1960-1 3⁄4 664 (700-1 3⁄4)	2000-2 1⁄4 704 (800-2 1⁄4)	2240-3 944 (1000-3)

ELEV 1296

D

TDZE 1287

MIRL Rwy 13-31
TDZL/RCLS Rwy 35R
HIRL Rwys 17L-35R and 17R-35L
REIL Rwys 13 and 31

OKLAHOMA CITY, OKLAHOMA

Amtd 3E 30NOV23

35°24'N-97°36'W

OKC WILL ROGERS INTL (OKC)

ILS or LOC RWY 17L