

LOC/DME I-SZK

111.1

Chan 48

APP CRS

072°

Rwy Idg

6800

TDZE

1175

Apt Elev

1175

LDA Y RWY 6

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

RADAR required for procedure entry. ADF required.
DME or RADAR required for LOC only.

▼

▲

❄️-12° C

For inop ALS, increase S-LDA 6 visibility Cats A/B to 1 3/8 SM.
Circling NA northwest of Rwy 6-24. Inop table does not apply to S-LDA 6 Cats C and D. Inop table does not apply to S-LDA/GS 6 all Cats.

MALSR

MISSED APPROACH: Climb to 2200 then climbing right turn to 5000 direct VIT NDB and hold, continue climb-in-hold to 5000.

ATIS

132.375

ROANOKE APP CON

133.225 339.8

ROANOKE TOWER

118.3 257.8

GND CON

121.9 257.8

LDA/GLIDE SLOPE

One Minute Holding Pattern

VGSI and LDA glidepath not coincident (VGSI Angle 3.00/TCH 58).

EXUNE I-SZK 15.4 RADAR

SAGE I-SZK 12.7 RADAR

RAMKE I-SZK 9.9 RADAR

SKIRT OM I-SZK 4.9 RADAR

JOKNI I-SZK 1.4

5600 ← 252°

5300 → 072°

GS 3.00° TCH 55

4500

4300

2680

2.7 NM

2.7 NM

5 NM

3.5

1.2

2200

5000

VIT

6800 X 150

5810 X 150

0.4% UP

TWR

072°

CATEGORY	A	B	C	D
S-LDA/GS 6	1857-2		682 (700-2)	
S-LDA 6	1880-1 705 (800-1)		1880-2 705 (800-2)	
CIRCLING	1880-1½ 705 (800-1½)		2460-3 1285 (1300-3)	2800-3 1625 (1700-3)

ELEV 1175

TDZE 1175

REIL Rwys 6 and 24

HIRL Rwys 6-24 and 16-34

FAF to MAP 8.5 NM

Knots	60	90	120	150	180
Min:Sec	8:30	5:40	4:15	3:24	2:50

ROANOKE, VIRGINIA

Amtd 13 05SEP24

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

37°20'N-79°59'W

LDA Y RWY 6