

APP CRS
336°

Rwy Ldg
TDZE
1160

Apt Elev
1175

RNAV (RNP) Z RWY 34

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

RNP AR APCH. RF required.

⚠

Missed approach requires RNP less than 1.0. For inop ALS, increase RNP 0.30 * all Cats visibility to 1½ SM.

❄-12°C

Inop table does not apply to RNP 0.30.

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C.

MALSR

AS

MISSED APPROACH: Climb to 6000 on track 336° to DMOSS, right turn to SETHB, right turn to JEEVY and on track 093° to PROSE and hold. * Missed approach requires minimum climb of 350 feet per NM to 4100. # Missed approach requires minimum climb of 415 feet per NM to 4100.

ATIS 132.375	ROANOKE APP CON 133.225 339.8	ROANOKE TOWER 118.3 257.8	GND CON 121.9 257.8
------------------------	---	-------------------------------------	-------------------------------

MSA RW34 25 NM
[5700]

DANCO 5600 094° (23.5) → (IAF) AYEAY 5200 094° (9.7) → (IF) SAMBE 210K → (FAF) NAVBE 3800 15.9 (6.4) → (IF) KAGEE 4500 094° (4.7) → DMOSS 336° (6.2) → SETHB (6.5) → JEEVY (3.5) 093° (8.5) → PROSE 250° 070° (5 NM) → (IF) SCHER 4000 269° (7) → (IF) HARDN 210K → 4000 269° (9.4) → (IAF) MCHL → (IF) ZIPAX 326° (1.6) → (IF) PIGGS 300° (1.6) → (IAF) PIGGS

Procedure NA for arrivals at PIGGS on V258 southeast bound, V136 southeast bound, and V222 southwest bound.

ELEV 1175

D

TDZE 1160

6000

DMOSS

↑ tr 336°

SETHB

JEEVY

PROSE

NAVBE 3800

See planview for multiple IF locations.

GP 3.00°

TCH 56°

8.2 NM

CATEGORY	A	B	C	D
RNP 0.15 DA #	1495-½	335 (400-½)		
RNP 0.30 DA*	1646-1	486 (500-1)		
RNP 0.30 DA	2115-4	955 (1000-4)		

AUTHORIZATION REQUIRED

ROANOKE, VIRGINIA

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

Orig 15AUG19

37°20'N-79°59'W

RNAV (RNP) Z RWY 34