

LOC/DME I-GWQ	APP CRS	28R	28L
<u>111.7</u>	284°	Rwy Ldg 11236	10275
Chan 54		TDZE 13	13
		Apt Elev 13	13

ILS or LOC RWY 28R
SAN FRANCISCO INTL (SFO)

RNAV 1-GPS or RADAR required for procedure entry.

- V** Circling NA to Rwy 10L, 10R, 19L, and 19R. Circling Rwy 1L, 1R NA at night. LOC procedure NA during simultaneous operations. For inop ALS increase S-LOC 28R* Cot C/D visibility to 1 3/8 SM. Simultaneous approach authorized. Simultaneous operations require use of vertical guidance; maintain last assigned altitude until established on glideslope.


ALSF-2
Rwy 28L

MALSR
Rwy 28L


MISSED APPROACH: Climb to 3000 on SFO VOR/DME R-281 to VIKYU INT/SFO 12 DME and hold.

*Missed approach requires minimum climb of 350 feet per NM to 1900; if unable to meet climb gradient, see ILS or LOC RWY 28L.

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8	CLNC DEL 118.2	CPDLC
---------------------------------	-------------------------------	------------------------------------	------------------	-------------------	-------



ELEV 13	D	TDZE 28R 13
HIRL all Rwy's		TDZE 28L 13
TDZ/CL Rwy's 19L and 28R		
REIL Rwy's 1L, 1R and 10L		



3000
↑
SFO R-281

VIKYU INT

Use I-GWQ DME when on the localizer course.
VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 68).

CEPIN INT
I-GWQ 12

I-GWQ 2

I-GWQ 3.2

AXMUL INT
I-GWQ 7.4

1800

28.4°

3000

1800

GS 3.00°
TCH 55

1.3 NM

4.2 NM

4.6 NM

CATEGORY	A	B	C	D
S-ILS 28R*	213/18 200 (200-½)			
S-LOC 28R*	480/24	467 (500-½)	480/50	467 (500-1)
SIDESTEP* 28L	480/55 467 (500-1)			480-1½ 467 (500-1½)
C CIRCLING	740-1 727 (800-1)	960-1¼ 947 (1000-1¼)	1560-3 1547 (1600-3)	NA