

LOC/DME I-SNA
111.75
Chan **54**(Y)

APP CRS
016°

Rwy Ldg **5700**
TDZE **56**
Apt Elev **56**

LOC BC RWY 2L
JOHN WAYNE/ORANGE COUNTY (SNA)

Circling Rwy 20L NA at night.

MISSED APPROACH: Climb to 800 then climbing left turn to 2600 direct SLI VORTAC and hold.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER★ 126.8 (CTAF) 343.625	GND CON 120.8	UNICOM 122.95
------------------------	-------------------------------------	---	-------------------------	-------------------------

SEAL BEACH
115.7 SU
Chan 104

BACK COURSE

113.6 JAX
Chan 83

120° 300°
R-120

120° 300°
R-122

120° 300°
R-123

120° 300°
R-123

ZUSED I-SNA
0.5

185±

WUNAD INT I-SNA 1.8

LOCALIZER 111.75
I-SNA
Chan 54(Y)

NEWPO INT I-SNA 4.5

1600 016°
(2.4)

(IF/IAF) MINOE I-SNA 10.9
3000 210K

196°

MSA SLI 25 NM
7700 4400 7000 2900
140° 230° 320° 050°

ELEV 56 D TDZE 56

REIL Rwy 20L
MIRL Rwy 2R-20L
HIRL Rwy 2L-20R

MINOE I-SNA 10.9
3000
VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 75).
NEWPO INT I-SNA 4.5
WUNAD INT I-SNA 1.8
ZUSED I-SNA 0.5
I-SNA DME ANTENNA
800 2600 SLI
Disregard GS indications.
6.4 NM 2.7 NM 1.3 NM 0.7 NM
560
016°
3.00° TCH 55
5700 x 150 ft
0.3% Up
2886 x 175
016°

CATEGORY	A	B	C	D
S-LOC 2L	560-1	504 (600-1)	560-1 3/8	504 (600-1 3/8)
CIRCLING	640-1	584 (600-1)	840-2 1/4 784 (800-2 1/4)	1180-3 1124 (1200-3)
WUNAD FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 2L	480-1	424 (500-1)	480-1 1/4	424 (500-1 1/4)
CIRCLING	640-1	584 (600-1)	840-2 1/4 784 (800-2 1/4)	1180-3 1124 (1200-3)

FAF to MAP 3.9 NM

Knots	60	90	120	150	180
Min:Sec	3:54	2:36	1:57	1:34	1:18

SANTA ANA, CALIFORNIA
Amdt 14A 12JUN25

JOHN WAYNE/ORANGE COUNTY (SNA)
33°41'N-117°52'W

LOC BC RWY 2L