

WAAS CH 40311 W01A	APP CRS 005°	Rwy Ldg TDZE 62 Apt Elev 62
--	------------------------	---

RNAV (GPS) RWY 1

SEBRING RGNL (SEF)

RNP APCH-GPS.

▼



⚠


NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use VRB altimeter setting; increase LPV DA to 503 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 530 feet and all visibilities ¾ SM; increase all MDAs 140 feet and LNAV visibility Cats C and D ¾ SM, increase Circling visibility Cat C ½ SM and visibility Cat D ¼ SM. Circling Rwy 14 NA at night. VDP and Baro-VNAV NA when using VRB altimeter. Rwy 1 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 600 then climbing left turn to 2000 direct EMBRU and hold.

AWOS-3 119.475	MIAMI CENTER 134.55 257.7	UNICOM 122.7 (CTAF)
--------------------------	-------------------------------------	-------------------------------



600	2000	EMBRU	4 NM Holding Pattern		
					
					
CATEGORY	A		B	C	D
LPV DA	381-1 319 (400-1)				
LNAV/VNAV DA	408-1½ 346 (400-1½)				
LNAV MDA	540-1 478 (500-1)		540-1¾ 478 (500-1¾)		
CIRCLING	600-1 538 (600-1)		600-1½ 538 (600-½)	880-2¾ 818 (900-2¾)	