

ILS or LOC Y RWY 18L

LOC I-VAD 109.3	APCH CRS 183°	Rwy Idg TDZE Arprt Elev 233 233	[USAF]	MOODY AFB (KVAD)
---------------------------	-------------------------	---	--------	------------------

RADAR or DME required

▼ * When ALS inop, increase RVR to 40 and vis to ¾ mile.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1½ miles.

ALSF-1

MISSED APPROACH: Climb to 3000 on VAD TACAN R-183 to EQUIP and hold.

ATIS ★ 273.5	VALDOSTA APP CON 126.6 285.6	TOWER ★ 128.45 (CTAF) 257.625	GND CON 138.95 275.8	CLNC DEL 120.625 296.7
------------------------	--	---	--------------------------------	----------------------------------

EMERG SAFE ALT 100 NM 3300

3000 VAD R-183	EQUIP VAD 16	VGSI and descent angles not coincident (VGSI angle 3.00/TCH 41).
-------------------	--------------	--

ELEV 233	TDZE 233
----------	----------

CATEGORY	A	B	C	D	E
S-ILS 18L*	433/24 200 (200-½)				
S-LOC 18L**	680/24 447 (500-½)		680/45 447 (500-¾)		
CIRCLING	760-1 527 (600-1)		760-1½ 527 (600-1½)		800-2 567 (600-2)

FAF to MAP 4.3 NM					
Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:22