

PALM BEACH FOUR DEPARTURE

PALM BEACH INTL (PBI)
WEST PALM BEACH, FLORIDA

PALM BEACH DEP CON
128.3 317.4 (N)
127.35 343.6 (S)
D-ATIS
123.75
CLNC DEL
121.6 284.6
GND CON
121.9 284.6
PALM BEACH TOWER
119.1 257.8

RADAR and DME required.

TOP ALTITUDE:
ASSIGNED BY ATC

ORLANDO
112.2 ORL
Chan 59

BAIRN

MATLK

SARASOTA
117.0 SRQ
Chan 117

JAYMC

LEE COUNTY
114.15 RSW
Chan 88(Y)

SWAGS

FORT LAUDERDALE
114.4 FLL
Chan 91

TAKEOFF MINIMUMS

Rwy 14, 32: Standard.

Rwy 10L: Standard with minimum climb of 720'/NM to 416.


Takeoff must occur no later than 2000' prior to DER.

Do not exceed 210K until established north-northwest bound.

Rwy 10R: Standard with minimum climb of 350'/NM to 414. Do not exceed 150K until established south-southwest bound.

Rwy 28L/R: Standard with minimum climb of 210'/NM to 1800.

VIRGINIA KEY
117.1 VKZ
Chan 118



NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RUNWAYS: Climb on assigned heading for RADAR vectors to filed or assigned route. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.