



WAAS CH 78332 W26A	APP CRS 261°	Rwy Idg 6330 TDZE 587 Apt Elev 595
--	------------------------	---


RNAV (GPS) RWY 26
SAN MARCOS RGNL (HYI)

Baro-VNAV NA when using New Braunfels altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (3°F) or above 54°C (130°F). When local altimeter setting not received, use New Braunfels altimeter setting and increase all DA 43 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats, and LNAV Cat C/D/E visibility 1/8 mile and Circling Cat C/D visibility 1/4 mile. Circling NA for Cat E SW of Rwy 13-31. DME/DME RNP-0.3 NA. VDP NA with New Braunfels altimeter setting. Helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:
Climb to 3000 direct
RAJRY and hold.

ATIS 120.825	AUSTIN APP CON 119.0 370.85	SAN MARCOS TOWER ★ 126.825 (CTAF) 0	GND CON 120.125
------------------------	---------------------------------------	--	---------------------------



3000	RAJRY					6 NM Holding Pattern
						
*LNAV only.		TUROC 2.4 NM to RW26	NAKIC 2000	QIMIB	081° → 3000 ← 261°	
						
		*1.3 NM to RW26	*1400	2000	GP 3.00° TCH 55	
1.3 NM		1.1 NM	1.9 NM	7.2 NM		
CATEGORY	A	B	C	D	E	
LPV DA	837- ³ / ₄ 250 (300- ³ / ₄)					
LNAV/ VNAV DA	866- ⁷ / ₈ 279 (300- ⁷ / ₈)					
LNAV MDA	1060-1	473 (500-1)	1060-1 ³ / ₈ 473 (500-1 ³ / ₈)			
CIRCLING	1080-1 485 (500-1)	1120-1 525 (600-1)	1240-1 ³ / ₄ 645 (700-1 ³ / ₄)	1320-2 ¹ / ₄ 725 (800-2 ¹ / ₄)	1340-2 ³ / ₄ 745 (800-2 ³ / ₄)	