

WAAS
CH **58299**
W01A

APP CRS
006°

Rwy Ldg
TDZE **6431**
Apt Elev **6451**

RNAV (GPS) X RWY 1
JACKSON HOLE (JAC)

RNP APCH-GPS.
Circling NA east of Rwy 1-19. Baro-VNAV NA.
Circling NA for Cat D. Inop table does not apply to LPV, LPV*, LNAV/VNAV, and LNAV Cat C/D.
-21°C

MALS
A2

MISSED APPROACH: Climb to 14000 direct QUIRT and on track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.
*Missed approach requires minimum climb of 385 feet per NM to 7700.

D-ATIS 120.625	SALT LAKE CENTER 133.25 285.6	JACKSON TOWER* 118.075 (CTAF) 0	GND CON 124.55	UNICOM 122.95
--------------------------	---	---	--------------------------	-------------------------



HOMVA 7 NM Holding Pattern		VALCU	DECEV	14000	QUIRT	tr 088°	DNW
17500 ← 186°							
11700 → 006°							
GP 3.00° TCH 50							
← 4.3 NM		← 3.7 NM	← 5.5 NM	← 4.1 NM	← 2.1 NM	← 3.4	
CATEGORY	A	B	C	D			
LPV DA*	6651/40 220 (200-¾)						
LPV DA	7445-4 1014 (1000-4)						
LNAV/VNAV DA	7327-4 896 (900-4)						
LNAV MDA	7540/55 1109 (1100-1)	7540-1¼ 1109 (1100-1¼)	7540-3 1109 (1100-3)				
CIRCLING	7540-1¼ 1089 (1100-1¼)	7540-1½ 1089 (1100-1½)	7560-3 1109 (1200-3)	NA			

14000

QUIRT

tr
088°

DNW

7 NM

HOMVA

VALCU

DECEV

17500

11700

GP 3.00°
TCH 50

← 4.3 NM

← 3.7 NM

← 5.5 NM

← 4.1 NM

← 2.1 NM

← 3.4

CATEGORY

A

B

C

D

LPV DA*

6651/40 220 (200-¾)

LPV DA

7445-4 1014 (1000-4)

LNAV/VNAV DA

7327-4 896 (900-4)

LNAV MDA

7540/55
1109 (1100-1)

7540-1¼
1109 (1100-1¼)

7540-3
1109 (1100-3)

CIRCLING

7540-1¼
1089 (1100-1¼)

7540-1½
1089 (1100-1½)

7560-3
1109 (1200-3)

NA

14000

QUIRT

tr
088°

DNW

7 NM

HOMVA

VALCU

DECEV

17500

11700

GP 3.00°
TCH 50

← 4.3 NM

← 3.7 NM

← 5.5 NM

← 4.1 NM

← 2.1 NM

← 3.4

CATEGORY

A

B

C

D

LPV DA*

6651/40 220 (200-¾)

LPV DA

7445-4 1014 (1000-4)

LNAV/VNAV DA

7327-4 896 (900-4)

LNAV MDA

7540/55
1109 (1100-1)

7540-1¼
1109 (1100-1¼)

7540-3
1109 (1100-3)

CIRCLING

7540-1¼
1089 (1100-1¼)

7540-1½
1089 (1100-1½)

7560-3
1109 (1200-3)

NA

TWR

3300 x 150

088° UP

006°