


WAAS CH 81809 W22A	APP CRS 223°	Rwy Ldg TDZE Apt Elev	8001 598 598
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22
ABRAHAM LINCOLN CAPITAL (SPI)

RNP APCH - GPS.				MALSR 	MISSED APPROACH: Climb to 2700 direct COVAC and hold.
ASR	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter not received, use Lincoln altimeter setting: increase LPV DA to 942 feet and all visibilities ½ SM, LNAV/VNAV DA to 1108 feet and all visibilities ½ SM; increase all MDAs 60 feet and visibility LNAV and Circling Cat C/D ¼ SM. Baro-VNAV and VDP NA when using Lincoln altimeter setting. For inop ALS, increase LPV all Cats visibility to ¾ SM. For inop ALS when using Lincoln altimeter setting, increase LPV all Cats visibility to 1 SM, increase LNAV/VNAV all Cats visibility to 1½ SM.				
ATIS	SAINT LOUIS APP CON	SPRINGFIELD TOWER ★	GND CON	UNICOM	
127.65 270.1	126.15 323.0	121.3 (CTAF) 0 257.8	121.9 348.6	122.95	



ELEV 598

D

TDZE 598

2700

↑

COVAC

1 NM to RW22

DETLE

2200

223°

1 NM

3.8 NM

6.2 NM

REYCO

4 NM Holding Pattern

043°

2600

223°

GP 3.00°

TCH 54

CATEGORY	A	B	C	D
LPV DA	884-½		286 (300-½)	
LNAV/VNAV DA	1050-¾		452 (500-¾)	
LNAV MDA	980-½	382 (400-½)	980-⅝	382 (400-⅝)
CIRCLING	1040-1¼ 442 (500-1¼)	1100-1¼ 502 (600-1¼)	1360-2¼ 762 (800-2¼)	1380-2½ 782 (800-2½)

223°

800 X 150

7399 X 150

AS

AS

AS

2700

↑

COVAC

1 NM to RW22

DETLE

2200

223°

1 NM

3.8 NM

6.2 NM

REYCO

4 NM Holding Pattern

043°

2600

223°

GP 3.00°

TCH 54

REIL Rwy 13

HIRL Rwys 4-22 and 13-31