

LOC/DME I-MPV	APP CRS	Rwy Ldg	5000
108.7	168°	TDZE	1135
Chan 24		Apt Elev	1166

ILS or LOC RWY 17

EDWARD F KNAPP STATE (MPV)

▼

NA

NA

19°C



NA

Inoperative table does not apply to S-LOC 17 Cats A and B. When local altimeter setting not received, procedure NA. Rwy 17 helicopter visibility reduction below ¾ SM
NA. Circling Rwy 5, 35 NA at night. For inoperative MALSR, increase S-ILS 17 all Cats visibility to 1½ mile and WANUX fix minimums S-LOC 17 Cats A/B visibility to 1 mile and Cats C/D visibility to 1½ mile.

MALSR

MISSED APPROACH:
Climb to 5200 direct MPV VOR/DME and hold, continue climb-in-hold to 5200.

ASOS	BOSTON CENTER	UNICOM
132.675	135.7 282.2	122.8 (CTAF) 0



REGGI VGSi and ILS glidepath not coincident (VGSi Angle 3.00/TCH 46).				
I-MPV 18.5 JIPDO INT I-MPV 14.6 ZAXOL INT I-MPV 10.5 WANUX I-MPV 6.7 OAKEN I-MPV 2.5 *LOC only				
GS 3.00° TCH 50				
Use I-MPV DME when on the Localizer course.				
3.9 NM 4.2 NM 3.8 NM 4.2 NM 0.8 0.8				
CATEGORY	A	B	C	D
S-ILS 17	1486-¾ 351 (400-¾)			
S-LOC 17	2980-1¼ 1845 (1900-1¼)	2980-1½ 1845 (1900-1½)	2980-3	1845 (1900-3)
CIRCLING	2980-1¼ 1814 (1900-1¼)	2980-1½ 1814 (1900-1½)	2980-3	1814 (1900-3)
WANUX FIX MINIMUMS				
S-LOC 17	1660-¾	525 (500-¾)	1660-1¼	525 (500-1¼)
CIRCLING	1980-1¼	814 (900-1¼)	2700-3 1534 (1600-3)	2920-3 1754 (1800-3)