



LOC I-JLN 110.3	APP CRS 134°	Rwy Ldg 5813 TDZE 970 Apt Elev 978
---------------------------	------------------------	---

ILS or LOC RWY 13
JOPLIN RGNL (JLN)

ADF required for LOC only. RADAR required.	MALSF	MISSED APPROACH: Climb to 3100 on I-JLN LOC localizer course southeast to HOVIL/RADAR and hold.
Autopilot coupled approach NA below 1147. Inop table does not apply to S-ILS 13 all Cats. MALSF (NSTD) 1368'.		

ATIS 120.85	KANSAS CITY CENTER 128.6 282.325	JOPLIN TOWER* 119.8 (CTAF) 0	GND CON 121.6	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



Remain within 10 NM		JL LOM LUNNS	6000	3100	HOVIL RADAR
2700		134°	2178	I-JLN SE crs	
GS 3.00° TCH 40		2200	3.7 NM		
CATEGORY	A	B	C	D	
S-ILS 13	1170/40		200 (200-¾)		
S-LOC 13	1300/40		330 (400-¾)		
CIRCLING	1460-1 482 (500-1)	1500-1 522 (600-1)	1540-1½ 562 (600-1½)	1580-2 602 (700-2)	

NC-3, 22 JAN 2026 to 19 FEB 2026

NC-3, 22 JAN 2026 to 19 FEB 2026