



LOC/DME I-HCE	APP CRS	Rwy Ldg	9000
110.5	355°	TDZE	480
Chan 42		Apt Elev	542

ILS or LOC RWY 36R
AUSTIN-BERGSTROM INTL (AUS)

DME required. RADAR required for procedure entry.	MALSR AS	MISSED APPROACH: Climb to 1000 then climbing right turn to 3000 on heading 030° and CWK VORTAC R-088 to HOOKK/CWK 17 DME and hold.
Simultaneous approach authorized. For inop ALS, increase S-ILS 36R Cat E visibility to RVR 4000, S-LOC 36R Cat C/D/E visibility to 1¾ SM.		

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (E) 120.875 270.25 (S) 119.0 370.85 (W)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6
-----------------	--	-----------------------------	------------------------



1000 ↑	3000 hdg 030°	CWK R-088	HOOKK △	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 59).	
CATEGORY	A	B	C	D	E
S-ILS 36R	680/18 200 (200-½)				
S-LOC 36R	1000/24 520 (500-½)	1000/55 520 (500-1)			
CIRCLING	1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	NA