

WAAS CH 77519 W04A	APP CRS 044°	Rwy Ldg 11010 TDZE 13 Apt Elev 13
--	------------------------	--

RNAV (GPS) Y RWY 4L


JOHN F KENNEDY INTL (JFK)

RNP APCH.

Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.

MISSED APPROACH: (Do not exceed 210K until BARJR) Climb to 3000 direct BARJR and track 067° to DUFFY and hold.

(SW)	D-ATIS (NE)	NEW YORK APP CON	KENNEDY TOWER	GND CON
115.4	117.7 128.725	128.125 269.0	119.1 281.55 (4R/22L and 13L/31R) 123.9 281.55 (4L/22R and 13R/31L)	121.9 348.6



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).


3000 BARJR tr 067° DUFFY

REPPE 2000 044° KRSTL 1500 RW04L

GP 3.00° TCH 57

6.5 NM 3.3 NM 1.2 NM

CATEGORY	A	B	C	D
LPV DA	232/40		219 (300-¾)	
LNAV/VNAV DA	329/50		316 (400-1)	
LNAV MDA	480/55 467 (500-1)		480-1⅜ 467 (500-1⅜)	
CIRCLING	640-1 627 (700-1)		680-1¾ 667 (700-1¾) 680-2 667 (700-2)	



NE-2, 22 JAN 2026 to 19 FEB 2026

NE-2, 22 JAN 2026 to 19 FEB 2026