

WAAS  
CH **42899**  
**W10A**

APP CRS  
**104°**

Rwy Ldg  
TDZE **5516**  
Apt Elev **5516**

**RNAV (GPS) RWY 10**

CENTRAL WYOMING RGNL (RIW)

▼

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lander altimeter setting and increase all DA 54 feet and all MDA 60 feet, and increase LPV and LNAV/VNAV all Cats visibility ¼ mile and increase LNAV Cat C/D visibility ½ mile. Baro-VNAV and VDP NA when using Lander altimeter setting. Rwy 10 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27°C (-16°F) or above 48°C (118°F).

MISSED APPROACH: Climb to 8600 direct DONVY and hold.

|                        |                                         |                                 |
|------------------------|-----------------------------------------|---------------------------------|
| ASOS<br><b>121.425</b> | SALT LAKE CENTER<br><b>133.25 285.6</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|------------------------|-----------------------------------------|---------------------------------|

ELEV 5516

**D**

TDZE 5516

104°

1.1% DOWN

1.7% DOWN

0.4% UP

0.7% UP

AS

REIL Rws 1, 10 and 19 **0**  
MIRL Rwy 1-19 **0**  
HIRL Rwy 10-28 **0**

|                      |                      |             |              |              |
|----------------------|----------------------|-------------|--------------|--------------|
| 7 NM Holding Pattern | TIDHU                | SAHKA       | 8600         | DONVY        |
| 7900                 | 6800                 |             |              |              |
| GP 3.00°             |                      |             |              |              |
| TCH 50               |                      |             |              |              |
|                      | 6.1 NM               | 2.7 NM      | 1.2          |              |
| CATEGORY             | A                    | B           | C            | D            |
| LPV DA               | 5902-1¼ 386 (400-1¼) |             |              |              |
| LNAV/VNAV DA         | 5965-1½ 449 (500-1½) |             |              |              |
| LNAV MDA             | 5940-1               | 424 (500-1) | 5940-1¼      | 424 (500-1¼) |
| CIRCLING             | 6000-1               | 484 (500-1) | 6000-1½      | 6120-2       |
|                      |                      |             | 484 (500-1½) | 604 (700-2)  |

RIVERTON, WYOMING

Amdt 2B 12OCT17

43°04'N-108°28'W

CENTRAL WYOMING RGNL (RIW)

**RNAV (GPS) RWY 10**