

WAAS CH 63236 W10B	APP CRS 096°	Rwy Ldg TDZE 14 Apt Elev 65
--	------------------------	---

RNAV (GPS) RWY 10R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP APCH-GPS.

▼


⚠

LNAV procedure NA during simultaneous operations. Rwy 10R helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7° C or above 54° C. For inop ALS, increase LNAV Cats C and D visibility to 1½ SM. Use of FD or AP required during simultaneous operations

MALSF

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 direct ULSUZ and hold.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4
------------------------	---------------------------------------	---	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).				
4 NM Holding Pattern BEZER BLAIM LORII ZALAL 1.8 NM to RWY 10R 1.2 NM to RWY 10R RWY 10R				
6000 4000 276° 096° 096° 3000 1800 620 800 2000 ULSUZ				
GP 3.00° TCH 51 3.3 NM 3.8 NM 3.7 NM 0.6 1.2				
CATEGORY	A	B	C	D
LPV DA	264/40		250 (200-¾)	
LNAV/VNAV DA	355/40		341 (300-¾)	
LNAV MDA	460/40	446 (400-¾)	460/55	446 (400-1)
CIRCLING	680-1	615 (700-1)	800-2 735 (800-2)	800-2¼ 735 (800-2¼)

ELEV 65 D TDZE 14

HIRL Rwy 10L-28R and 10R-28L

SE-3, 22 JAN 2026 to 19 FEB 2026

SE-3, 22 JAN 2026 to 19 FEB 2026