

WAAS CH 69208 W33B	APP CRS 335°	Rwy Ldg TDZE 124 Apt Elev 143
--	------------------------	---

BALTIMORE/ **RNAV (GPS) RWY 33R**

WASHINGTON INTL THURGOOD MARSHALL (BWI)


RNP APCH - GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. For inop MALSR, increase LNAV/VNAV all Cats visibility to RVR 5000 and LNAV all Cats visibility to RVR 5500. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. Helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to LPV, all Cats.

MALSR

MISSED APPROACH:
Climb to 3000 direct
KRENE and hold.

D-ATIS 115.1 127.8	POTOMAC APP CON 119.0 282.275 (020°-100°) 124.55 317.425 (101°-130°)	119.7 290.475 (131°-180°) 128.7 307.9 (181°-019°)	BALTIMORE TOWER 119.4 257.8	GND CON 121.9	CLNC DEL 118.05
------------------------------	--	--	---------------------------------------	-------------------------	---------------------------



3000

DUDDS

3000

335°

GP 3.00°
TCH 47

EXEVE
2.5 NM to
RW33R

ORIOL
2000

1.1 NM to
RW33R

1.4 NM

3.3 NM

6.3 NM

940

2000

CATEGORY	A	B	C	D
LPV DA	333/40	209 (200-¾)	NA	
LNAV/VNAV DA	406/40	282 (300-¾)	NA	
LNAV MDA	520/40	396 (400-¾)	NA	
CIRCLING	640-1 497 (500-1)	660-1 517 (600-1)	NA	

TDZ/CL Rwy 10 and 33L
REIL Rwy 15L and 33R
HIRL all Rwy