

APP CRS
233°

Rwy Ldg
TDZE
931

Apt Elev
947

RNAV (RNP) Z RWY 23

WEST VIRGINIA INTL YEAGER (CRW)

▼

▲

For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM.

ALSF-1

Ⓐ

Ⓜ

MISSED APPROACH:

Climb to 4000 on track 233° to CITMA and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6
----------------------	--	--	-------------------------------

ELEV 947

D

TDZE 931

6 NM

233°

053°

CITMA

4000

tr 233°

⬆

⬇

See planview for multiple IF locations.

COSIK

2400

RW23

233°

2400

GP 3.00°

TCH 56

6000

359°

11.3

⬆

⬇

(IAF) SCRIB (RF REQD)

6000

095°

19.3

⬆

⬇

(IAF) RULEY (RF REQD)

4000

265°

8.6

⬆

⬇

(IAF) ITALY

4000

174°

11.9

⬆

⬇

(IAF) KETTA

4000

049°

9.2

⬆

⬇

(IAF) CHARLESTON HVQ (RF REQD)

4000

233°

13.5

⬆

⬇

Procedure NA for arrival on HVQ VOR/DME airway radials 337 CW 141.

4000

tr 233°

⬆

⬇

CITMA

⬆

⬇

See planview for multiple IF locations.

COSIK

2400

RW23

233°

2400

GP 3.00°

TCH 56

6000

359°

11.3

⬆

⬇

(IAF) SCRIB (RF REQD)

6000

095°

19.3

⬆

⬇

(IAF) RULEY (RF REQD)

4000

265°

8.6

⬆

⬇

(IAF) ITALY

4000

174°

11.9

⬆

⬇

(IAF) KETTA

4000

049°

9.2

⬆

⬇

(IAF) CHARLESTON HVQ (RF REQD)

4000

233°

13.5

⬆

⬇

Procedure NA for arrival on HVQ VOR/DME airway radials 337 CW 141.

CATEGORY	A	B	C	D
RNP 0.30	DA	1419/60	488 (500-1¼)	

AUTHORIZATION REQUIRED

HIRL Rwy 5-23
REIL Rwy 5

CHARLESTON, WEST VIRGINIA

Orig-C 07SEP23

38°23'N-81°36'W

WEST VIRGINIA INTL YEAGER (CRW)

RNAV (RNP) Z RWY 23