


SAN DIEGO, CALIFORNIA

LOC/DME I-NKX 111.15 Chan 48(Y)	APCH CRS 243°	Rwy ldg 8001	24L 12,000	24R 475
		TDZE 477		
		Arpt Elev 477		

[USN]

MIRAMAR MCAS (JOE FOSS FLD) (KNKX)

DME and RADAR required			ALSIF-1 	MISSED APPROACH: Climb to 1500, then climbing right turn to 3000 via heading 340°. Expect radar vectors.	
▼ ** When ALS inop, increase vis to ¾ mile. ** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 ½ miles. *** CAT E circling not authorized S of Rwy 6R-24L.					
ATIS ★ 133.475 352.0	SOCAL APP CON 132.2 269.1	FOSS TOWER ★ 135.2 298.925 0	GND CON 128.625 307.325	LA CENTER 291.7	ASR/ PAR



EMERG SAFE ALT 100 NM 13,600

		ELEV 477		TDZE 24L 477 TDZE 24R 475	
		HOMAD I-NKX 8		JARMO I-NKX 11.8	
		RYNNO I-NKX 14.7		TUPOC I-NKX 3.2	
		WEVIM I-NKX 2		ZENPA I-NKX 0.6	
		GS 3.00°		TCH 53	
		0.4		1.4 NM	
		1.2 NM		4.8 NM	
CATEGORY	A	B	C	D	E
S-ILS 24R*	675 - ½		200	(200- ½)	
S-LOC 24R**	920- ½	445 (500- ½)	920- ¾	445	(500- ¾)
SIDESTEP 24L	920-1	443 (500-1)	920-1 ½	443 (500-1 ½)	920-2
CIRCLING***	940-1	463 (500-1)	960-1	483 (500-1)	960-1 ½
	463 (500-1)	483 (500-1)	483 (500-1 ½)	703 (800-2 ¼)	883 (900-3)

SAN DIEGO, CALIFORNIA

32° 52' N - 117° 09' W

MIRAMAR MCAS (JOE FOSS FLD) (KNKX)

Amtd 1 29DEC22

ILS Z or LOC/DME Z RWY 24R

SW-3, 22 JAN 2026 to 19 FEB 2026

SW-3, 22 JAN 2026 to 19 FEB 2026