

WAAS CH 63209 W27A	APP CRS 275°	Rwy Ldg 11002 TDZE 45 Apt Elev 55
--	------------------------	--

RNAV (GPS) RWY 27R
ORLANDO SANFORD INTL (SFB)

ORLANDO SANFORD INTL (SFB)


T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C (32°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
For inop ALS, increase LNAV/VNAV all Cats visibility to 1 1/4 SM, increase LNAV Cat C/D visibility to 1 SM.

MALSR




MISSED APPROACH:
Climb to 2000 direct
UGMAH and hold.

ATIS 125.975	ORLANDO APP CON 135.3 351.9 (N) 125.225 351.9 (S)	SANFORD TOWER ★ 120.3 (CTAF) 0 254.35	GND CON 121.35 254.35
------------------------	---	---	---------------------------------



ELEV 55	D	TDZE 45
---------	----------	---------



***LNAV only.**

CATEGORY	A	B	C	D
LPV DA	245-½	200 (200-½)		
LNAV/VNAV DA	425-⅞	380 (400-⅞)		
LNAV MDA	420-½	375 (400-½)	420-⅝	375 (400-⅝)
CIRCLING	580-1	525 (600-1)	600-1½ 545 (600-1½)	640-2 585 (600-2)

RNAV (GPS) RWY 27R