


LOC/DME I-ALO 111.7 Chan 54	APP CRS 128°	Rwy Ldg 8399 TDZE 873 Apt Elev 873
---	------------------------	---


ILS or LOC RWY 12
WATERLOO RGNL (A.O)

DME or RADAR required. ▼ For inop ALS, increase S-LOC 12 ZESOP FIX MINIMUMS Cats C/D visibility to RVR 5500. ▲ #RVR 1800 authorized with the use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 1400 then climbing left turn to 3300 on ALO VOR/DME R-096 to DEWAR INT/ALO VOR/DME 10.8 DME and hold.
--	-----------	--

ATIS 120.65	DES MOINES APP CON ★ 118.9 251.15	WATERLOO TOWER ★ 125.075 (CTAF) 0 257.8	GND CON 121.9 269.1	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



Use I-ALO DME when on localizer course.				
One Minute Holding Pattern EYUCE I-ALO 14 RADAR CULCA I-ALO 7.6 RADAR ZESOP I-ALO 3.3 DEWAR				
5000 3400 ←308° 128°→ GS 3.00° TCH 55 2800 2800 *1420 1 NM *LOC only				
CATEGORY	A	B	C	D
S-ILS 12 #	1073/24 200 (200-½)			
S-LOC 12	1420/24 547 (600-½)		1420/60 547 (600-1¼)	
CIRCLING	1420-1 547 (600-1)		1480-1¾ 607 (700-1¾) 1600-2¼ 727 (800-2¼)	
ZESOP FIX MINIMUMS (DME REQUIRED)				
S-LOC 12	1240/24 367 (400-½)		1240/35 367 (400-¾)	
CIRCLING	1360-1 487 (500-1) 1400-1 527 (600-1)		1480-1¾ 607 (700-1¾) 1600-2¼ 727 (800-2¼)	



NC-3, 22 JAN 2026 to 19 FEB 2026

NC-3, 22 JAN 2026 to 19 FEB 2026