

WAAS CH 61219 W01A	APP CRS 016°	Rwy Ldg 10302 TDZE 1314 Apt Elev 1333
--	------------------------	--

RNAV (GPS) Y RWY 1L


WICHITA DWIGHT D EISENHOWER NTL (ICT')

⚠ Inoperative table does not apply to LNAV Cat D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). For inoperative ALSF-2, increase LNAV Cat C/D visibility to RVR 4500. DME/DME RNP-0.3 NA. Simultaneous approach authorized with ILS or LOC RWY 1R. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

MISSED APPROACH:
Climb to 3600 direct ACUBO and hold.

ATIS 125.15	WICHITA APP CON 126.7 353.5	WICHITA TOWER 118.2 257.8	GND CON 121.9 348.6
-----------------------	---------------------------------------	-------------------------------------	-------------------------------



ELEV 1333		D		TDZE 1314	
HIRL all Rwys					
REIL Rwy 14 and 32					
TDZ/CL Rwy 1L					
CATEGORY	A	B	C	D	
LPV DA	1514/18		200 (200-½)		
LNAV/VNAV DA	1615/24		301 (300-½)		
LNAV MDA	1620/24		306 (300-½)		
CIRCLING	1800-1 467 (500-1)		1980-1¾ 647 (700-1¾)		1980-2 647 (700-2)

NC-2, 22 JAN 2026 to 19 FEB 2026

NC-2, 22 JAN 2026 to 19 FEB 2026