

LOC I-FLG	APP CRS	Rwy Ldg
110.5	214°	7000
		7003
		Apt Elev
		7014

ILS or LOC RWY 21

FLAGSTAFF PULLIAM (FLG)

Autopilot coupled approach NA below 7640 feet. DME required. DME from FLG VOR/DME. Simultaneous reception of I-FLG and FLG DME required. For inop ALS increase S-ILS 21 all Cats visibility to %.

⚠

MALSR

MISSED APPROACH: Climb to 7500, then climbing left turn to 11000 on heading 130° and FLG R-172 to OATES INT/FLG VOR/DME 16.7 DME and hold, continue climb-in-hold to 11000.

ATIS	PHOENIX APP CON	FLAGSTAFF TOWER ★	GND CON	UNICOM
125.8	126.375 236.775	134.55 (CTAF) 239.25	121.9	122.95

7500	11000	FLG	OATES	FAP	10200	12300
↑	hdg 130°	R-172	△	FLG 10.2	034°	214°
* LOC only	* FLG 1.3	HEV MU				
	SOLBE	FLG 0.9				
	8500*					
	0.4	0.5	3.7 NM	5.3 NM		
CATEGORY	A	B	C	D		
S-ILS 21	7258-1/2	255 (300-1/2)				
S-LOC 21	7340-1/2	337 (400-1/2)				
CIRCLING	7520-1 506 (600-1)	7560-1 546 (600-1)	8100-3 1086 (1100-3)	8560-3 1546 (1600-3)		

FLAGSTAFF, ARIZONA

Amtd 1 07DEC17

35°08'N-111°40'W

FLAGSTAFF PULLIAM (FLG)

ILS or LOC RWY 21