




ILS or LOC RWY 9R
OAKLAND COUNTY INTL (PTK)

▼ Circling Rwy 9L, 36 NA at night. When local altimeter setting not received: see Coleman A Young Muni altimeter setting and increase DA to 1286 feet and all MDA 120 feet, increase S-LOC 9R Cat B visibility to RVR 4000, Cat C/D visibility $\frac{3}{8}$ SM, and Circling Cat B/C/D visibility $\frac{1}{2}$ SM. For inop MALSR, increase S-LOC 9R Cat C/D visibility to $\frac{1}{4}$ SM. For inop MALSR, when using Coleman A Young altimeter, increase S-HS 9R all Cats visibility to RVR 4500, and increase S-LOC 9R Cat C/D visibility to 2 SM. **RVR 1800 authorized with the use of FD or AP or HUD to DA, NA when using Coleman A Young Muni altimeter setting.



MISSED APPROACH:
Climb to 1600 then
climbing right turn
to 3000 direct SVM
VORTAC and hold.

ATIS 125.025	DETROIT APP CON 132.35 284.0	PONTIAC TOWER ★ 120.5 (CTAF) 0	GND CON 121.9	UNICOM 122.95
-----------------	---------------------------------	-----------------------------------	------------------	------------------



EC-1, 22 JAN 2026 to 19 FEB 2026