

WAAS CH 45502 W15A	APP CRS 154°	Rwy Ldg 10702 TDZE 16 Apt Elev 17
--	------------------------	--

RNAV (GPS) RWY 15
CHENNAULT INTL (CWF)

RNP APCH - GPS

⚠ Baro-VNAV and VDP NA when using Lake Charles Rgnl altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase LPV DA to 232 feet; increase LNAV/VNAV DA to 523 feet; increase all MDAs to 20 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM. For inop ALS when using Lake Charles Rgnl altimeter setting increase LNAV/VNAV visibility all Cats to 1½ SM.

MALSR



MISSED APPROACH: Climb to 2000 direct FERDU and hold.

ATIS 120.0	LAKE CHARLES APP CON★ 119.8 282.3	CHENNAULT TOWER★ 124.2 (CTAF) 0 290.4	GND CON 121.65 275.8	UNICOM 122.95
----------------------	---	---	--------------------------------	-------------------------

