

WAAS CH 50311 W05A	APP CRS 050°	Rwy Idg TDZE Apt Elev	3999 1906 1915
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 5

POCONO MOUNTAINS RGNL (MPO)


▼

⚠

Baro-VNAV NA when using Wilkes-Barre/Scranton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F). DME/DME RNP-0.3 NA. Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Wilkes-Barre/Scranton altimeter setting: increase LPV DA to 2339 feet, LNAV/VNAV DA to 2431 feet and all visibilities ¼ SM; increase all MDAs 180 feet and visibility Cat C and D ½ SM. Circling Rwy 23 NA at night.

MISSED APPROACH:
Climb to 4000 direct ZEGAS and left turn via 292° track to LVZ VORTAC and hold.

ASOS 120.275	WILKES-BARRE APP CON 126.3 256.7	CLNC DEL 125.3	UNICOM 122.7 (CTAF) 0
------------------------	--	--------------------------	---------------------------------



ELEV 1915

TDZE 1906

Procedure Turn NA

VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 43).

4000

ZEGAS

292° tr

LVZ

WIBUM

4000

050°

WOSIT

YONUP 2.1 NM to RW05

RW05

*2600

3400

6 NM

2.4 NM

2.1 NM

GP 3.00°

TCH 60

*LNAV only

CATEGORY	A	B	C	D
LPV DA	2160-1		254 (300-1)	
LNAV/VNAV DA	2252-1¼		346 (400-1¼)	
LNAV MDA	2320-1	414 (500-1)	2320-1¼	414 (500-1¼)
CIRCLING	2480-1	2500-1	2600-2	2660-2½
	565 (600-1)	585 (600-1)	685 (700-2)	745 (800-2½)

REIL Rwys 5, 13, 23, and 31 0

MIRL Rwys 5-23 and 13-31 0