

LOC I-OUT 111.5	APP CRS 274°	Rwy Ldg TDZE Apt Elev 6500 778 778
---------------------------	------------------------	--

ILS or LOC RWY 27
ELKHART MUNI (EKM)

RNP APCH - GPS. RADAR required for procedure entry.	MALS R	MISSED APPROACH: Climb to 1500 then climbing right turn to 4000 direct JJANN and hold.
⚠ Circling NA to Rwy 8 and 26. Rwy 27 helicopter visibility reduction below RVR 4000 NA. ⚠ Circling Rwy 18 and 36 NA at night. When local altimeter setting not received, use SBN altimeter setting and increase S-ILS 27 DA to 1100 feet, increase all MDAs 40 feet, and S-LOC 27 visibility Cat C/D to RVR 5500, and Circling visibility Cat D ½ SM. For inop ALS, increase S-ILS 27 all Cats visibility to RVR 4500 and S-LOC 27 Cat A/B visibility to 5500 and Cat C/D visibility to 1½ SM. For inop ALS when using SBN, increase S-LOC 27 Cat A/B visibility to RVR 5500, and Cat C/D visibility to 1½ SM.		

AWOS-3 124.475	SOUTH BEND APP CON ★ 118.55 257.8	ELKHART TOWER ★ 119.5 (CTAF) 0	GND CON 121.8	UNICOM 122.95
--------------------------	---	--	-------------------------	-------------------------

