

WAAS CH 50118 W12A	APP CRS 123°	Rwy Ldg TDZE 2583 Apt Elev 2583
--	------------------------	---

RNAV (GPS) RWY 12

MC COOK BEN NELSON RGNL (MCK)

▼

▲

Circling NA to Rwy 17 and 35. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Baro-VNAV and VDP NA when using Imperial Muni altimeter setting.


For inoperative MALSR, increase LPV all Cats visibility to 1¾, and LNAV visibility Cat A to 1. Inoperative table does not apply to LNAV/VNAV. When local altimeter setting not received, use Imperial Muni altimeter setting and increase all DAs 213 feet, and LPV all Cats visibility ¾ mile, LNAV/VNAV Cat C visibility ½ mile; increase all MDAs 220 feet, and LNAV and Circling visibility Cats A and B ¼ mile, Cat C 1 mile.

MALSR


MISSED APPROACH:

Climb to 5000 direct OPUXE and hold.

ASOS 119.025	DENVER CENTER 132.7 226.675	UNICOM 122.8 (CTAF) 0
------------------------	---------------------------------------	---------------------------------



Procedure NA for arrival at QWILT on V220 westbound.



CATEGORY	A	B	C	D
LPV DA	2840-½	257 (300-½)		NA
LNAV/VNAV DA	3240-2	657 (700-2)		NA
LNAV MDA	3180-½	597 (600-½)	3180-1 597 (600-1)	NA
CIRCLING	3180-1	597 (600-1)	3360-2¼ 777 (800-2¼)	NA

