

|                |             |          |             |
|----------------|-------------|----------|-------------|
| VORTAC EUF     | APP CRS     | Rwy Ldg  | <b>5000</b> |
| <b>109.2</b>   | <b>187°</b> | TDZE     | <b>285</b>  |
| Chan <b>29</b> |             | Apt Elev | <b>285</b>  |

VOR RWY 18  
WEEDON FLD (EUF)

**NA** When local altimeter setting not received, use Columbus, GA altimeter setting and increase all MDAs 40 feet and S-18 visibility Cats C and D ½ SM and Circling Cats C and D ¼ SM. Increase AFENY fix minimums S-18 visibility Cats C and D ½ SM and Circling visibility Cats C and D ¼ SM.

**MISSED APPROACH:** Climb to 1500 then climbing right turn to 2000 direct EUF VORTAC and hold.

|                        |                                         |                                 |                                 |
|------------------------|-----------------------------------------|---------------------------------|---------------------------------|
| ASOS<br><b>128.325</b> | ATLANTA APP CON ★<br><b>125.5 323.1</b> | CLNC DEL<br><b>134.25 339.8</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|------------------------|-----------------------------------------|---------------------------------|---------------------------------|

