

WAAS CH 69423 W28A	APP CRS 284°	Rwy Ldg TDZE 1189 Apt Elev 1191
--	------------------------	---

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3PT 126.05	COLUMBUS APP CON 125.95 317.775	CLNC DEL 119.45	UNICOM 123.05 (CTAF) 0
---------------------------	---	---------------------------	---

MISSED APCH FIX

BONIF

4 NM

MSA RW 28 25 NM

3100

2800

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE 3000 099° (13.5)

2800 NoPT 014° (9.8) (IAF) TUCUG

2800 NoPT 305° (13.6) (IAF) ROSCO

ELEV 1191

TDZE 1189

5504 x 100

284°

3000

BONIF

*LNAV only

1 NM

0.7

2.9 NM

6.9 NM

1760

2700

6000

2800

GP 3.00°

TCH 40'

CATEGORY	A	B	C	D
LPV DA		1389-1	200 (200-1)	
LNAV/VNAV DA		1439-1	250 (300-1)	
LNAV MDA		1540-1	351 (400-1)	

MIRL Rwy 10-28 **0**

REIL Rwys 10 and 28 **0**