

APP CRS	Rwy Ldg	9000
267°	TDZE	96
	Apt Elev	96

RNAV (RNP) Y RWY 26R
GEORGE BUSH INTCNL/HOUSTON (IAH)

⚠ For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cnts visibility to RVR 5000 and increase RNP 0.15 all Cnts visibility to 1½ SM. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALS-F-2

A

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct PEPBI and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 120.725 290.2	GND CON 118.575
-------------------------	--	---------------------------------------	---------------------------

4 NM

345°

PEPBI

RADAR REQUIRED

5100 087° (3)

SKLER (IF) 6000 210K (RF REQD)

DRKAR

2600 to SOOPR (8.1)

SOOPR

267° (5.8)

RW26R

267°

CHUBS (7.2)

2600 to SOOPR 267° (1.8)

2000 267° (2.6)

3000 267° (4.2)

4000 267° (4.2)

5000 235° (3)

5000 267° (5)

NEWLY 5000

RAIDS (IF)

ZAPPO (IAF)

GRIZL

6000 200° (3.2)

HOOTI (IAF) 6000 210K

MSA RW26R 2.5 NM

3100

ELEV	96	D	TDZE	96
------	----	---	------	----

600

3000

PEPBI

See planview for multiple IF locations.

SOOPR

OWELL

2000

267°

2600

2000

RW26R

5.8 NM

2.6 NM

GP 3.00°

TCH 59

CATEGORY	A	B	C	D
RNP 0.11 DA		429/40	333 (400-¾)	
RNP 0.15 DA		496/45	400 (400-¾)	
RNP 0.30 DA		554/50	458 (500-1½)	

AUTHORIZATION REQUIRED

TDZ/CL Rwy 8R, 8L, 15R, 26R, 26L, 27 and 33L

HIRL all Rwy

SC-5, 22 JAN 2026 to 19 FEB 2026

SC-5, 22 JAN 2026 to 19 FEB 2026