

WAAS
CH **42521**
W20A

APP CRS
202°

Rwy Ldg
TDZE **772**
Apt Elev **772**

RNAV (GPS) RWY 20
MID-CAROLINA RGNL (RUQ)

25275

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C (4°F) or above 39°C (102°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lexington altimeter setting and increase all DA 37 feet and all MDA 40 feet, increase LNAV Cat C and D visibility ½ SM and Circling Cat C visibility ¼ SM and Circling Cat D ¼ SM. For inop ALS when using Lexington altimeter setting, increase LNAV Cat C and D visibility to 1¾ SM. VDP and Baro-VNAV NA when using Lexington altimeter setting. For inop ALS, increase LNAV/VNAV visibility to ¾ SM all Cats.

MALSR

MISSED APPROACH:
Climb to 2100 then climbing right turn to 3400 direct YIDPO and hold.

AWOS-3
118.175

CHARLOTTE APP CON
128.325 307.8

UNICOM
122.725 (CTAF) ①

ELEV 772

TDZE 772

*LNAV only.				
	1.7 NM	3.6 NM	7 NM	
CATEGORY	A	B	C	D
LPV DA	972-1½		200 (200-½)	
LNAV/VNAV DA	1032-½		260 (300-½)	
LNAV MDA	1360-½ 588 (600-½)		1360-1¼ 588 (600-1¼)	
CIRCLING	1360-1 588 (600-1)		1440-1¾ 668 (700-1¾)	

SALISBURY, NORTH CAROLINA

Amdt 1C 27FEB20

35°39'N-80°31'W

RNAV (GPS) RWY 20

MID-CAROLINA RGNL (RUQ)