


APP CRS	Rwy Ldg	5001
233°	TDZE	798
	Apt Elev	802

RNAV (GPS) RWY 23

LENAWEE COUNTY (ADG)

RNP APCH - GPS	MISSED APPROACH: Climb to 3000 direct OBIHI and hold.
Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Ann Arbor Muni altimeter setting: increase all MDA 80 feet and visibility LNAV Cats C/D and Circling Cats C/D ¼ SM. Circling NA to Rwys 11 and 29.	

ASOS 118.825	TOLEDO APP CON 134.35 317.55	UNICOM 122.8 (CTAF) 0
-----------------	---------------------------------	--------------------------



HIRL Rwy 5-23 **(L)**
 REIL Rwy 5 **(L)**

VGSI and descent angles not coincident
 (VGSI Angle 3.00/TCH 32).

CATEGORY	A	B	C	D
LNAV MDA	1260-1	462 (500-1)	1260-1 $\frac{3}{8}$ 462 (500-1 $\frac{3}{8}$)	1260-1 $\frac{1}{2}$ 462 (500-1 $\frac{1}{2}$)
CIRCLING	1300-1 498 (500-1)	1320-1 518 (600-1)	1340-1 $\frac{1}{2}$ 538 (600-1 $\frac{1}{2}$)	1440-2 638 (700-2)