

WAAS CH 70626 W14A	APP CRS 136°	Rwy Ldg TDZE Apt Elev	7701 27 30
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) Z RWY 14
JACKSONVILLE INTL (JAX)

RNP APCH-GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C . For inop ALS, increase LPV visibility all Cats to 3/4 SM and increase LNAV/VNAV visibility all Cats and LNAV Cats A and B visibility to 1 SM. Rwy 14 helicopter visibility reduction below 3/4 SM NA.

MALSR MISSED APPROACH:
Climb to 500 then climbing left turn to 2000 direct YEJWO and hold.

D-ATIS 125.85	JACKSONVILLE APP CON 119.0 269.9	JACKSONVILLE TOWER 118.3 317.7	GND CON 121.9 348.6
-------------------------	--	--	-------------------------------



4 NM

Holding Pattern

OSBAJ

2000

← 316°

→ 136°

GP 3.00°

TCH 54

VGSI and RNAV glidepath not coincident

(VGSI Angle 3.00/TCH 70).

WOLQU

1700

1700

1.2 NM to RW14

RW14

6.7 NM

3.9 NM

1.2

500

2000

YEJWO

CATEGORY	A	B	C	D
LPV DA		306-¾	279 (300-¾)	
LNAV/VNAV DA		388-¾	361 (400-¾)	
LNAV MDA	480-¾ 453 (500-¾)		480-⅞ 453 (500-⅞)	
CIRCLING	520-1 490 (500-1)		580-1½ 550 (600-1½)	580-2 550 (600-2)

