

CHINO, CALIFORNIA

AL-5599 (FAA)

25219

WAAS CH 97320 W26A	APP CRS 255°	Rwy Ldg 4858 TDZE 636 Apt Elev 650
--	------------------------	---


RNAV (GPS) RWY 26R
CHINO (CNO)

RNP APCH-GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below
A -16°C or above 54°C. Helicopter visibility reduction below $\frac{3}{4}$ SM NA.


MISSED APPROACH: Climb to 4000 direct IRUYI and via 241° track to LAHAB and hold.

D-ATIS 125.85	SOCAL APP CON 135.4 377.125	CHINO TOWER ★ 118.5 (CTAF)	GND CON 121.6	UNICOM 122.95
-------------------------	---------------------------------------	--------------------------------------	-------------------------	-------------------------




MISSED APCH FIX

LAHAB



ELEV 650

TDZE 636



REIL Rwy 3 and 21
MIRL Rwy 3-21 and 8R-26L
HIRL Rwy 8L-26R

4000 ↑	IRUYI ✦	tr 241° △	LAHAB	CAZBY 4 NM Holding Pattern
*NNAV only. DEWYE *1.8 NM to RW26R RW26R 255° 256° 3000 2100 076° → ← 256° 4400 GP 3.00° TCH 51				
1.8 2.6 NM 3.1 NM 5.9 NM				
CATEGORY	A	B	C	D
LPV DA	1030-1¼ 394 (400-1¼)			
NNAV/VNAV DA	1177-2 541 (600-2)			
LNAV MDA	1260-1 624 (700-1)	1260-1¾ 624 (700-1¾)	1260-2 624 (700-2)	
CIRCLING	1260-1¾ 610 (700-1¾)			1340-2¼ 690 (700-2¼)

CHINO, CALIFORNIA

Orig-E 07OCT21

CHINO (CNO)

33°58'N-117°38'W

RNAV (GPS) RWY 26R

SW-3, 22 JAN 2026 to 19 FEB 2026