

WAAS
CH **56304**
W16A

APP CRS
165°

Rwy Ldg
TDZE **1055**
Apt Elev **1060**

RNAV (GPS) RWY 16

ROSEAU MUNI/RUDY BILLBERG FLD (R.O.X)

RNP APCH - GPS.

⚠

Circling NA to Rwy's 6 and 24. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility to ¾ SM. Inop table does not apply to LPV all Cats.

MALSF

⚠

MISSED APPROACH: Climb to 2800
direct ACEBO and hold.

AWOS-3PT
118.075

MINNEAPOLIS CENTER
134.75 251.1

UNICOM
122.8 (CTAF) **0**

MISSED APCH FIX

ACEBO

165°

345°

5 NM

5 NM Holding Pattern

BADYA

6000

2800

345°

165°

GP 3.00°

TCH 44

CATPI

2700

1700

5.9 NM

3.1 NM

0.9 NM

1 NM

BATBY

1.9 NM to RW16

1 NM to RW16

RW16

2800

ACEBO

CATEGORY	A	B	C	D
LPV DA		1255-¾	200 (200-¾)	
LNAV/VNAV DA		1330-¾	275 (300-¾)	
LNAV MDA		1420-¾	365 (400-¾)	
CIRCLING	1600-1	540 (600-1)	1840-2¼ 780 (800-2¼)	1840-2½ 780 (800-2½)

ELEV 1060

TDZE 1055

165°

0.3% UP

4400 X 75

2097 X 250

34

MIRL Rwy 16-34 **0**

REIL Rwy 34 **0**

ROSEAU, MINNESOTA

Amtd 1 03NOV22

48°51'N-95°42'W

ROSEAU MUNI/RUDY BILLBERG FLD (R.O.X)

RNAV (GPS) RWY 16