


WAAS CH 42820 W08A	APP CRS 077°	Rwy Idg TDZE Apt Elev	7723 1274 1277
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 8
CENTRAL WISCONSIN (CWA)

RNP APCH - GPS.			MALSR 	MISSED APPROACH: Climb to 3000 direct ASARE and hold.	
 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cat C and D visibility to 1½ SM.					
ATIS 127.45	MINNEAPOLIS CENTER 124.4 317.7	CWA TOWER ★ 119.75 (CTAF)  360.7		GND CON 121.9 360.7	UNICOM 122.95



4 NM Holding Pattern		TUCYU	HENPA	WOKOS	ASARE
6000 ← 257°		3000 → 077°	3000	1.7 NM to RW08	3000
GP 3.00°		3000	1860	1.1 NM to RW08	ASARE
TCH 55		7.6 NM	3.6 NM	0.6 NM	1.1 NM
CATEGORY		A	B	C	D
LPV DA			1474-½	200 (200-½)	
LNAV/VNAV DA			1601-½	327 (400-½)	
LNAV MDA		1640-½	366 (400-½)	1640-¾	366 (400-¾)
CIRCLING		1740-1	463 (500-1)	1740-1½	1840-2

