

WAAS CH 40322 W21A	APP CRS 211°	Rwy Ldg TDZE Apt Elev	5500 1270 1270
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21

FOOTHILLS RGNL (MRN)

RNP APCH - GPS.



▼

Baro-VNAV and VDP NA when using HKY altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Rwy 21 helicopter visibility reduction below ¾ SM NA. When local altimeter not received, use HKY altimeter setting and increase LPV DA to 1562 feet; LNAV/VNAV DA to 1642 feet; increase all MDAs 60 feet and visibility LNAV Cats C and D and Circling Cat D ¼ SM.

⚠

MISSED APPROACH: Climb to 2000 then climbing right turn to 4400 direct CIKIS and hold.

AWOS-3P 124.175	ATLANTA CENTER 125.15 263.0	UNICOM 122.7 (CTAF) 0
---------------------------	---------------------------------------	---------------------------------



2000	4400	CIKIS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 48).			
		JAGUP 1.9 NM to RW21	CICAC	ZAGOK	CIKIS 5 NM Holding Pattern	
		1 NM to RW21	3000	3700	6000 4400	GP 3.00° TCH 45
		1920	3000			
		1 NM	0.9 NM	3.4 NM	2.9 NM	6.9 NM
CATEGORY	A		B		C	D
LPV DA			1520-1		250 (300-1)	
LNAV/VNAV DA			1600-1		330 (400-1)	
LNAV MDA	1680-1		410 (500-1)		1680-1½	410 (500-1½)
CIRCLING	1720-1 450 (500-1)		1760-1 490 (500-1)		1800-1½ 530 (600-1½)	2140-2¾ 870 (900-2¾)