

WAAS CH 42838 W22A	APP CRS 224°	Rwy Ldg TDZE Apt Elev	5001 979 979
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22

RICHARD DOWNING (I40)


⚠

⚠ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Zanesville altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Zanesville altimeter setting and increase LPV DA to 1291 feet and all visibilities ¼ SM, increase LNAV/VNAV DA to 1501 feet and all visibilities ½ SM, increase all MDA 80 feet and LNAV Cat C/D visibility ¼ SM, Circling Cat C/D visibility ½ SM.

MISSED APPROACH:
Climb to 1400 then climbing right turn to 3400 direct BEDDE and hold.

AWOS-3 118.875	INDIANAPOLIS CENTER 124.45 323.275	GCO 121.725	UNICOM 123.0 (CTAF)	122.9
--------------------------	--	-----------------------	-------------------------------	--------------



ELEV 979	TDZE 979
----------	----------

↑ 1400

↷ 3400

4 NM Holding Pattern

*LNAV only.

BPANE 2.6 NM to RW22

IRACU 2400

BEDDE

044° → 3400

← 224°

GP 3.00° TCH 45

224°

500' x 75'

REIL Rwy 22

MIRL Rwy 4-22

CATEGORY	A	B	C	D
LPV DA	1229-¾		250 (300-¾)	
LNAV/VNAV DA	1439-1½		460 (500-1½)	
LNAV MDA	1380-1	401 (500-1)	1380-1½	401 (500-1½)
CIRCLING	1440-1 461 (500-1)	1520-1 541 (600-1)	1780-2¼ 801 (900-2¼)	1780-2½ 801 (900-2½)