


WAAS CH 49040 W26A	APP CRS 255°	Rwy Idg TDZE 186 Apt Elev 193
--	------------------------	---

RNAV (GPS) RWY 26

TRACY MUNI (TCY)

RNP APCH. Baro-VNAV NA when using Stockton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling NA southwest of Rwy 12-30. Circling Rwy 30 NA at night. Rwy 26 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Stockton altimeter setting: increase LPV DA to 496 feet, increase LNAV/VNAV DA to 553 feet; increase all MDAs 60 feet and visibility LNAV Cat C ½ SM.	MISSED APPROACH: (Do not exceed 210K until OMWAP) Climb to 640 then climbing right turn to 3000 direct OMWAP and hold.
---	--

AWOS-3 118.375	NORCAL APP CON 123.85 278.3	UNICOM 123.075 (CTAF) 0
--------------------------	---------------------------------------	-----------------------------------



ELEV 193 TDZE 186		640 3000 OMWAP		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 21).		4 NM Holding Pattern	
MIRL Rwy 8-26 and 12-30 REIL Rwy 8, 12, 26 and 30		CATEGORY		A	B	C	D
		LPV DA		436-7/8	250 (300-7/8)		NA
		LNAV/VNAV DA		493-11/8	307 (300-11/8)		NA
		LNAV MDA		540-1	354 (400-1)		NA
		CIRCLING		580-1 387 (400-1)	660-1 467 (500-1)	660-1½ 467 (500-1½)	NA