

WAAS
CH **99600**
W36A

APP CRS
002°

Rwy Idg **8003**
TDZE **261**
Apt Elev **264**

RNAV (GPS) RWY 36


GOLDEN TRIANGLE RGNL (GTR)

RNP APCH.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Columbus AFB altimeter setting: increase LPV DA to 500 feet, LNAV/VNAV DA to 593 feet and LNAV/VNAV visibility ½ SM; increase all MDAs 40 feet. Baro-VNAV and VDP NA when using Columbus AFB altimeter setting.

MISSED APPROACH:
Climb to 3000 direct HUYKA and hold.

ATIS 126.375	COLUMBUS APP CON ★ 135.6 323.275	GOLDEN TRIANGLE TOWER ★ 118.2 (CTAF) 0 298.875	GND CON 135.375 322.475	CLNC DEL 135.375 322.475
------------------------	--	--	-----------------------------------	------------------------------------



ELEV 264

TDZE 261

7 NM Holding Pattern DIXVU

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).

3000 HUYKA

GP 3.00° TCH 42

6000
3000
182°
002°
002°
2000
BAWMO
2000
JAKVU
2.7 NM to RW36
*1 NM to RW36
RW36
*1140
6.3 NM
2.7 NM
1.7 NM
1 NM

*LNAV only.

7 NM Holding Pattern

GP 3.00° TCH 42

6000
3000
182°
002°
002°
2000
BAWMO
2000
JAKVU
2.7 NM to RW36
*1 NM to RW36
RW36
*1140
6.3 NM
2.7 NM
1.7 NM
1 NM

*LNAV only.

CATEGORY	A	B	C	D	E
LPV DA		461-3/4	200 (200-3/4)		
LNAV/VNAV DA		554-7/8	293 (300-7/8)		
LNAV MDA	640-1	379 (400-1)	640-1 1/8	379 (400-1 1/8)	
CIRCLING	760-1	496 (500-1)	960-2 696 (700-2)	960-2 1/4 696 (700-2 1/4)	960-2 1/2 696 (700-2 1/2)

8003 X 150

36

002° to RW36

HIRL Rwy 18-36 0