

WAAS CH 49009 W05A	APP CRS 052°	Rwy Ldg 7100 TDZE 89 Apt Elev 93
--	------------------------	---

RNAV (GPS) RWY 5
ALBERT J. ELLIS (OAJ)

A Baro-VNAV NA when using Wilmington altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP -0.3 NA. VDP NA with Wilmington altimeter setting. When local altimeter setting not received, use Wilmington altimeter setting and increase LPV DA to 383 feet; increase LNAV/VNAV DA to 559 feet and all visibilities ½ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ¾ SM. For inoperative MALSR, increase LNAV Cat C/D visibility to 1 mile. For inoperative MALSR, when using Wilmington altimeter setting, increase LPV all Cats visibility to ¾ mile, increase LNAV/VNAV all Cats to 1½ mile, and LNAV Cat C/D to 1¾ mile.

MALSR



MISSED APPROACH:
Climb to 900 then
climbing left turn to
2100 direct CUAL
and hold.

ATIS 124.475	WILMINGTON APP CON ★ 135.75 317.425	ELLIS TOWER ★ 132.65 (CTAF) 0	GND CON 125.4	UNICOM 122.95
-----------------	--	----------------------------------	------------------	------------------