


WAAS CH 78304 W21A	APP CRS 206°	Rwy Ldg TDZE 485 Apt Elev 485
--	------------------------	---

RNAV (GPS) RWY 21
ST CLAIR COUNTY (PLR)

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Anniston altimeter setting and increase LPV DA to 799 feet and all Cats visibility to 1, increase LNAV/VNAV DA to 964 feet and all visibilities to 1½, increase all MDA 80 feet and LNAV Cat C/D to 1¼ and Circling Cat C to 2½ and Cat D to 3. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Anniston altimeter setting.

MISSED APPROACH:
Climb to 4000 direct HANUR and hold, continue climb-in-hold to 4000.

AWOS-3P 119.625	BIRMINGHAM APP CON 123.8 256.8	UNICOM 123.05 (CTAF) 0
---------------------------	--	----------------------------------



ELEV 485	TDZE 485
-----------------	-----------------

4000 HANUR

*LNAV only.

UTACE 2.1 NM to RW21

EFBUB 2000

TADUW 4 NM Holding Pattern

026° 3500

206°

2000

1200*

1.4 NM 0.7 NM 2.5 NM 6.2 NM

GP 3.00° TCH 53

CATEGORY	A	B	C	D
LPV DA		735-¾	250 (300-¾)	
LNAV/VNAV DA		900-1¾	415 (500-1¾)	
LNAV MDA	980-1	495 (500-1)	980-1¾	495 (500-1¾)
CIRCLING	1180-1	695 (700-1)	1240-2¼ 755 (800-2¼)	1340-2¾ 855 (900-2¾)